

Model # 6' Canopy Table

1675 Locust Street
Red Bud, IL 62278
Phone: 618-282-8200
Fax: 618-282-8202

WARRANTY & TERMS

WARRANTY: 5 Year Limited Warranty on Thermoplastic coated elements. Ultra Play guarantees all items for one full year to be free of defects in workmanship or materials when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

ORDER INFORMATION: When ordering please include a brief description of all items. Be sure to include colors for UltraCoat and powder coated surfaces. To assist Ultra Play in entering orders properly, please fax or mail orders on your standard purchase order form. Quotes are good for 30 days.

GSA CONTRACT: GSA pricing is available on several items. Contact our sales department for specific information.

SPECIFICATIONS: Due to Ultra Play's continuous product improvement, we reserve the right to change specifications when necessary without notice.

PRICING: Ultra Play strives to keep pricing as low as possible. However, should we encounter increases in our costs that are simply too large to absorb, we reserve the right to increase prices without notice.

TERMS: Approved accounts net 30 days. Initial order requires payment in full before shipment. A finance charge of 1-1/2% per month wil be applied to all delinquent accounts. We accept VISA, MASTERCARD, and AMERICAN EXPRESS.

FREIGHT CHARGES: Terms of sale are F.O.B. factory. Ultra Play will prepay and add the freight to the invoice if requested to do so. All weights are approximate.


Damages or loss in transit is the responsibility of the carrier, whether visible or concealed. It is the responsibility of the recipient to assure that the order is received complete. Before signing the delivery receipt, inspect the shipment immediately and completely. Note any damages or shortages on the bill of lading. Damage reports must be filed within 10 days. Ultra Play is NOT responsible for damages or loss in transit. Title to all goods passes to the customer at the time of shipment. Ultra Play will assist in filing claims if the freight arrangements were made by Ultra Play at your request.

CANCELLATIONS AND RETURNS: Cancellations are only accepted with approval of Ultra Play. No merchandise shall be returned without a Return Goods Authorization number which is issued by customer service. Any authorized merchandise must be carefully packed and received in saleable condition. A restocking charge of up to 25% will be applied to all returned goods when the error is not the fault of Ultra Play. All returns must be shipped freight prepaid.


SAFETY WARNINGS & EQUIPMENT INSPECTION

- Owners and installers please note these safety warnings and make use of this checklist on a regular basis.
- Follow installation instructions when erecting equipment.
- Ground surfaces around equipment should be restored as needed. Concrete footings should never be exposed. Surface depth should comply with ASTM and CPSC specifications.
- Check for and repair damage caused by wear or vandalism, a major factor in injury causing situations.
- All protruding bolts should be covered or cut off and finished smooth. Sharp edges on pipes should be capped or removed. Check for bent, broken, or severly worn pipe, and replace.
- All equipment should be free of rust and repainted whenever necessary to deter rusting.
- We provide our customers with layout sheets and installation instructions. Please keep on file the specifications sheet that contains the listing of every part used.
- Never add components not intended for use with this product.
- Regular maintenance is necessary in this and all park and recreational equipment to insure the safety of the user.
- Note: Proper maintenance of equipment requires regular tightening of all bolts, nuts, and setscrews.
- Note: Regular checking of all parts, castings, etc. should be made. If a part is broken or worn, it shoud be replaced immediatly.
- Check to be sure all fittings are tight and that bars and pipes do not move.
- Replace all worn S-hooks. S-hooks must be completely closed. Failure to close S-hooks can result in serious injury to the user. NEVER reuse S-hooks.
- Test for free movement of swing hanger and other moving attached parts.
- Check for worn chains and replace them.
- A soft resilient surface should be placed under all swings extending at least twice the height of the top rail both front and back.


HARDWARE




7/16" x 5 1/2"
Machine Bolt




3/8" x 1 1/4"
Machine Bolt




5/16" x 1"
Machine Bolt




5/16" Flat
Washer




3/8" Flat
Washer




7/16" Flat
Washer



7/16"
Hex Nut




5/16"
Kep Nut




3/8" Kep
Nut


TOOLS REQUIRED




1/2", 9/16" and 5/8" Wrench



1/2", 9/16" and 5/8" Socket Wrench



Tape Measure



Level

Top & Seats: 11 gauge die formed angle frame 1”x1-7/8” with 3” radius corners. Seat and back plates are fabricated from a 12ga plate. Holes are precision punched at 5/8” diameter. 7 gauge x 1-1/2” flat bar center support and mounting bracket understructure. Electrically MIG welded.

Canopy: 12 ga. sheet steel precision punched with 5/8” diameter holes. Bracing is 3/16” steel plate. Ends are finished with 5/8" solid rod.

Coating: Oven fused functionalized polyethylene copolymer-based thermoplastic.
Fluidized bed coating application with superior mechanical performance,
impact resistance and UV-stability.


Frame: 4 x 4 x 11 gauge structural steel square tubing. Seat and top mounting points 7 gauge x 1-1/2” die stamped steel flat bar. Support attachment plates are 3/8" plate. All electrically MIG welded.

Frame Coating: Electrostatic powder coated application oven cured.

Hardware: All stainless steel hardware fasteners.


Dimensions: 6’ permanent picnic table w/ canopy design. Top is 30-1/8” wide x 72-1/8” long and is 30” high. Seats are 12-1/8” wide x 72-1/8” long and 18” high. Outside to outside table dimension is 64” x 72-1/8”. Installed dimensions are 78” x 88 ½” x 96”.

COMPONENTS




ITEM NO.	DESCRIPTION	Default /QTY.
1	table support	1
2	canopy post	2
3	6' Punched Seat	2
4	6' Punched Top	1
5	canopy	3
6	7/16" Zinc Plated Washer	48
7	3/8" Zinc Plated Washer	16
8	5/16" Zinc Plated Washer	32
9	7/16" x 5-1/2" Machine Bolt	24
10	3/8" x 1 1/4" Machine Bolt (Zinc)	8
11	5/16" x 1" Machine Bolt (Zinc)	16
12	7/16" Hex Nut (Zinc)	24
13	3/8" Kep Nut (SS)	8
14	337 Seat Mounting Plate	4
15	seat support arm	4
16	5/16" Kep Nut (SS)	16

STEP 1




Attach table support to canopy post using specified hardware

STEP 2




Bury posts in concrete footing.

STEP 3




Attach canopy to post.




Attach canopies together

STEP 4



Attach seat arms to table support. Repeat for all 4 arms.



Attach seats and top using specified hardware.

OVERALL DIMENSIONS

